# Product data sheet Characteristics

# NSYS3D121240DP

Wall mounted steel enclosure, PanelSeT S3D, double plain door, with mounting plate, 1200x1200x400mm, IP55, IK10



#### Main

Range	PanelSeT
Product name	PanelSeT S3D
Application	Multi-purpose
Category	Compact enclosure
Enclosure nominal height	47.2 in (1200 mm)
Enclosure nominal width	47.2 in (1200 mm)
Enclosure nominal depth	15.7 in (400 mm)
Door type	Solid
Mounting plate description	Plain
Type of gland plate	Standard
Installation accessory type	Wall-mounting
Device composition	1 body 2 cable gland plate 2 door with lock 1 mounting plate

#### Complementary

Complementary	
Body type	Single piece body
	Gutter-shaped front rail double sheet thickness
Number of doors	Front face 2
Door opening side	Reversible 120 °)
Lock type	3 points lock, 3 mm double-bar
Accessibility for operation	Front
Removable parts	Door by hinges
	Cable gland plate by screws
	Mounting plate by fixing element
Material	Enclosure steel
	Mounting plate galvanised steel
Surface finish	Enclosure epoxy-polyester powder
Color	Enclosure Gray RAL 7035)
Standards	IEC 62208
Product Certifications	UL[RETURN]GL[RETURN]BV[RETURN]DNV[RETURN]cUL
Net Weight	246.9 lb(US) (112 kg)

#### Environment

2111101111011C		
IK degree of protection	IK10 IEC 62262	
IP degree of protection	IP55 IEC 60529	

## Ordering and shipping details

Category	US10ES180034	
Discount Schedule	0ES1	
GTIN	3606480159954	
Returnability	No	
Country of origin	FR	

## Packing Units

3 - 3	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	17.7 in (45.0 cm)
Package 1 Width	48.03 in (122.0 cm)
Package 1 Length	52.4 in (133.0 cm)
Package 1 Weight	246.9 lb(US) (112.0 kg)

## Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	☐ China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

### Contractual warranty

	•	
Warranty		18 months