Product data sheet

Specifications





Metal industrial box plain door H150xW150xD120 IP66 IK10 RAL 7035

NSYSBM151512

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 46.80 USD

Main

| Range | Spacial | |
|--------------------------|---------------------------------------|--|
| Product Name | Spacial SBM | |
| Device Application | Multi-purpose | |
| Category | Industrial box | |
| Device Short Name | SBM | |
| Enclosure Type | Flat face box | |
| Enclosure Nominal Height | 5.91 in (150 mm) | |
| Enclosure Nominal Width | 5.91 in (150 mm) | |
| Enclosure Nominal Depth | 4.72 in (120 mm) | |
| Enclosure Mounting | Wall mounted | |
| Device Composition | 4 cover screw 1 cover 1 body | |
| Body Type | Single piece body folded and welded | |
| Type Of Front Cover | Plain door | |
| Cover Fixing | Half turn metal screw | |
| Lock Type | Captive screw PZ2 outside sealed area | |
| Removable Parts | Cover by captive screws | |

Complementary

| Material | sheet steel | |
|-------------------------------------|--------------------------------------|--|
| Surface Finish | Polyester powder | |
| Color | Gray RAL 7035) | |
| Standards | IEC 62208 | |
| Product Certifications | LR DNV-GL UL BV | |
| Ip Degree Of Protection | IP66 IEC 60529 | |
| Ik Degree Of Protection | tection IK10 conforming to IEC 62262 | |
| Ambient Air Temperature For Storage | -31140 °F (-3560 °C) | |
| Operating Temperature | -31176 °F (-3580 °C) | |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Ordering and shipping details

| Category | US10ES180033 |
|-------------------|---------------|
| Discount Schedule | 0ES1 |
| Gtin | 3606480520105 |
| Returnability | Yes |
| Country Of Origin | ES |

Packing Units

| Unit Type Of Package 1 | PCE |
|------------------------------|---------------------------|
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 5.51 in (14.0 cm) |
| Package 1 Width | 6.69 in (17.0 cm) |
| Package 1 Length | 6.69 in (17.0 cm) |
| Package 1 Weight | 2.88 lb(US) (1.306 kg) |
| Unit Type Of Package 2 | P12 |
| Number Of Units In Package 2 | 120 |
| Package 2 Height | 24.02 in (61.0 cm) |
| Package 2 Width | 31.50 in (80.0 cm) |
| Package 2 Length | 47.24 in (120.0 cm) |
| Package 2 Weight | 367.55 lb(US) (166.72 kg) |

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

| ⊘ | Reach Free Of Svhc | |
|----------|----------------------------|-----|
| ⊘ | Toxic Heavy Metal Free | |
| ⊘ | Mercury Free | |
| ⊘ | Rohs Exemption Information | Yes |

Certifications & Standards

| Reach Regulation | REACh Declaration |
|--------------------------|---|
| Eu Rohs Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| China Rohs Regulation | China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope) |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |