

Product data sheet

Specifications



Metal industrial box plain door H200xW300xD80 IP66 IK10 RAL 7035

NSYSBM20308

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 67.68 USD

Main

Range	Spacial
Product Name	Spacial SBM
Device Application	Multi-purpose
Category	Industrial box
Device Short Name	SBM
Enclosure Type	Flat face box
Enclosure Nominal Height	7.87 in (200 mm)
Enclosure Nominal Width	11.81 in (300 mm)
Enclosure Nominal Depth	3.15 in (80 mm)
Enclosure Mounting	Wall mounted
Device Composition	4 cover screw 1 cover 1 body
Body Type	Single piece body folded and welded
Type Of Front Cover	Plain door
Cover Fixing	Half turn metal screw
Lock Type	Captive screw PZ2 outside sealed area
Removable Parts	Cover by captive screws

Complementary

Material	sheet steel
Surface Finish	Polyester powder
Color	Gray RAL 7035)
Standards	IEC 62208
Product Certifications	LR DNV-GL UL BV
Ip Degree Of Protection	IP66 IEC 60529
Ik Degree Of Protection	IK10 conforming to IEC 62262
Ambient Air Temperature For Storage	-31...140 °F (-35...60 °C)
Operating Temperature	-31...176 °F (-35...80 °C)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Net Weight	4.69 lb(US) (2.128 kg)
------------	------------------------

Ordering and shipping details

Category	US10ES180033
----------	--------------

Discount Schedule	0ES1
-------------------	------

Gtin	3606480520068
------	---------------

Returnability	No
---------------	----

Country Of Origin	IN
-------------------	----

Packing Units

Unit Type Of Package 1	PCE
------------------------	-----

Number Of Units In Package 1	1
------------------------------	---

Package 1 Height	3.74 in (9.5 cm)
------------------	------------------

Package 1 Width	8.46 in (21.5 cm)
-----------------	-------------------

Package 1 Length	12.40 in (31.5 cm)
------------------	--------------------

Package 1 Weight	4.69 lb(US) (2.128 kg)
------------------	------------------------

Unit Type Of Package 2	P12
------------------------	-----

Number Of Units In Package 2	112
------------------------------	-----

Package 2 Height	41.34 in (105.0 cm)
------------------	---------------------

Package 2 Width	31.50 in (80.0 cm)
-----------------	--------------------

Package 2 Length	47.24 in (120.0 cm)
------------------	---------------------

Package 2 Weight	548.95 lb(US) (249.0 kg)
------------------	--------------------------

Contractual warranty

Warranty	18 months
----------	-----------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

Well-being performance

Reach Free Of Svhc

Toxic Heavy Metal Free

Mercury Free

Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation

[REACH Declaration](#)

Eu Rohs Directive

Pro-active compliance (Product out of EU RoHS legal scope)

[EU RoHS Declaration](#)

China Rohs Regulation

[China RoHS declaration](#)

Pro-active China RoHS declaration (out of China RoHS legal scope)

Environmental Disclosure

[Product Environmental Profile](#)

Circularity Profile

No need of specific recycling operations