



Main

Range	Thalassa
Product name	Thalassa TBP
Device Application	Multi-purpose
Category	Industrial box
Height	5.4 in (138 mm)
Width	3.7 in (93 mm)
Depth	2.8 in (72 mm)
Internal height	4.9 in (125 mm)
Internal width	3.1 in (80 mm)
Internal depth	2.6 in (65 mm)
Enclosure mounting	Wall mounted
Device composition	1 body 1 cover 4 cover screw
Quantity per Set	Set of 2
Body type	One piece moulded
Type of front cover	Low plain cover
Cover fixing	Plastic screws
Lock type	Captive screw flat outside sealed area
Removable parts	Cover by captive screws

Complementary

Material	polycarbonate
Color	Gray RAL 7035)
Standards	UL 508 A IEC 62208
Product Certifications	TÜV[RETURN]UL
Electrical Insulation Class	Class II
Mounting location	Outdoor (with canopy or shelter and anticondensation valve)
Net Weight	0.55 lb(US) (0.25 kg)

Environment

IP degree of protection	IP66 conforming to NEMA 4.4X
IK degree of protection	IK08 conforming to IEC 62262
Fire resistance	1760.0000000000 °F (960 °C)
Ambient Air Temperature for Storage	5...140 °F (-15...60 °C)
Operating temperature	-13.0000000000...176.0000000000 °F (-25...80 °C)

Ordering and shipping details

Category	US10ES180033
Discount Schedule	0ES1
GTIN	3606480165627
Returnability	No
Country of origin	HU

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.67 in (4.25 cm)
Package 1 Width	2.85 in (7.25 cm)
Package 1 Length	4.04 in (10.25 cm)
Package 1 Weight	8.9 oz (252 g)
Unit Type of Package 2	P12
Number of Units in Package 2	696
Package 2 Height	47.2 in (120 cm)
Package 2 Width	31.5 in (80 cm)
Package 2 Length	53.1 in (135 cm)
Package 2 Weight	465.2 lb(US) (211 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Contractual warranty

Warranty	18 months
----------	-----------