NSYTBP292416HT

PC box IP66 IK08 RAL7035 Int.H275W225D160 Ext.H291W241D168 Transp.cover H60



Main

Range	Thalassa
Product name	Thalassa TBP
Device Application	Multi-purpose
Category	Industrial box
Height	11.5 in (291 mm)
Width	9.5 in (241 mm)
Depth	6.6 in (168 mm)
Internal height	10.8 in (275 mm)
Internal width	8.9 in (225 mm)
Internal depth	6.3 in (160 mm)
Enclosure mounting	Wall mounted
Device composition	1 body
	1 cover
	4 cover screw
Body type	One piece moulded
Type of front cover	High transparent cover
Cover fixing	Plastic screws
Lock type	Captive screw flat outside sealed area
Removable parts	Cover by captive screws

Complementary

Material	polycarbonate
Color	Gray RAL 7035)
	Transparent
Standards	UL 508 A
	IEC 62208
Product Certifications	TÜV[RETURN]UL
Electrical Insulation Class	Class II
Mounting location	Outdoor (with canopy or shelter and anticondensation valve)
Net Weight	2.95 lb(US) (1.34 kg)

Environment

IP degree of protection	IP66 conforming to NEMA 4.4X
IK degree of protection	IK08 conforming to IEC 62262
Fire resistance	1760.0000000000 °F (960 °C)
Ambient Air Temperature for Storage	5140 °F (-1560 °C)
Operating temperature	-13.0000000000176.00000000000 °F (-2580 °C)

Ordering and shipping details

Category	US10ES180033	
Discount Schedule	0ES1	
GTIN	3606480165917	
Returnability	No	
Country of origin	HU	

Packing Units

•	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.3 in (18.5 cm)
Package 1 Width	9.8 in (25 cm)
Package 1 Length	12.2 in (31 cm)
Package 1 Weight	2.95 lb(US) (1.34 kg)
Unit Type of Package 2	P12
Number of Units in Package 2	48
Package 2 Height	47.2 in (120 cm)
Package 2 Width	31.5 in (80 cm)
Package 2 Length	53.5 in (136 cm)
Package 2 Weight	205.03 lb(US) (93 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EVEL RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	☐ China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Contractual warranty

Warranty	18 months