# **Product data sheet**

Specifications





## ABS box IP66 IK07 RAL7035 Int.H105W105D125 Ext.H116W116D133 Opaque cover H80

NSYTBS111113H

Product availability: Non-Stock - Not normally stocked in distribution facility

Price\*: 12.40 USD

#### Main

Range	Thalassa	
Product Name	Thalassa TBS	
Device Application	Multi-purpose	
Category	Industrial box	
Height	4.57 in (116 mm)	
Width	4.57 in (116 mm)	
Depth	5.24 in (133 mm)	
Internal Height	4.13 in (105 mm)	
Internal Width	4.13 in (105 mm)	
Internal Depth	4.92 in (125 mm)	
Enclosure Mounting	Wall mounted	
Device Composition	1 body 1 cover 4 cover screw	
Quantity Per Set	Set of 2	
Body Type	One piece moulded	
Type Of Front Cover	High plain cover	
Cover Fixing	Plastic screws	
Lock Type	Captive screw flat outside sealed area	
Removable Parts	Cover by captive screws	

### Complementary

Material	ABS (acrylonitrile butadiene-styrene)	
Color	Gray RAL 7035)	
Standards	IEC 62208	
Product Certifications	TÜV	
Electrical Insulation Class	Class II	
Ip Degree Of Protection	IP66 conforming to NEMA 4.4X	
Ik Degree Of Protection	IK07 conforming to IEC 62262	
Glow Wire Resistance	1202 °F (650 °C) IEC 60695-2-11	

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Ambient Air Temperature For Storage	5104 °F (-1540 °C)
Operating Temperature	-13140 °F (-2560 °C)
Net Weight	0.53 lb(US) (0.24 kg)

# Ordering and shipping details

Category	US10ES180033
Discount Schedule	0ES1
Gtin	3606480165245
Returnability	No
Country Of Origin	HU

### **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	4.72 in (12 cm)
Package 1 Width	4.72 in (12 cm)
Package 1 Length	13.39 in (34 cm)
Package 1 Weight	8.47 oz (240 g)
Unit Type Of Package 2	P12
Number Of Units In Package 2	360
Package 2 Height	47.24 in (120 cm)
Package 2 Width	31.50 in (80 cm)
Package 2 Length	53.15 in (135 cm)
Package 2 Weight	235.89 lb(US) (107 kg)

## **Contractual warranty**

Warranty 18 months



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

### Well-being performance

<b>⊘</b>	Reach Free Of Svhc	
<b>⊘</b>	Toxic Heavy Metal Free	
<b>⊘</b>	Mercury Free	
<b>⊘</b>	Rohs Exemption Information	Yes

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
China Rohs Regulation	China RoHS declaration  Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations