

Product data sheet

Specifications



ABS box IP66 IK07 RAL7035
Int.H105W105D55
Ext.H116W116D62 Opaque cover
H10

NSYTBS11116

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 7.21 USD

Main

Range	Thalassa
Product Name	Thalassa TBS
Device Application	Multi-purpose
Category	Industrial box
Height	4.57 in (116 mm)
Width	4.57 in (116 mm)
Depth	2.44 in (62 mm)
Internal Height	4.13 in (105 mm)
Internal Width	4.13 in (105 mm)
Internal Depth	2.17 in (55 mm)
Enclosure Mounting	Wall mounted
Device Composition	1 body 1 cover 4 cover screw
Quantity Per Set	Set of 5
Body Type	One piece moulded
Type Of Front Cover	Low plain cover
Cover Fixing	Plastic screws
Lock Type	Captive screw flat outside sealed area
Removable Parts	Cover by captive screws

Complementary

Material	ABS (acrylonitrile butadiene-styrene)
Color	Gray RAL 7035)
Standards	IEC 62208
Product Certifications	TÜV
Electrical Insulation Class	Class II
Ip Degree Of Protection	IP66 conforming to NEMA 4.4X
Ik Degree Of Protection	IK07 conforming to IEC 62262
Glow Wire Resistance	1202 °F (650 °C) IEC 60695-2-11

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Ambient Air Temperature For Storage	5...104 °F (-15...40 °C)
Operating Temperature	-13...140 °F (-25...60 °C)
Net Weight	0.33 lb(US) (0.151 kg)

Ordering and shipping details

Category	US10ES180033
Discount Schedule	0ES1
Gtin	3606480165252
Returnability	No
Country Of Origin	HU

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	2.40 in (6.1 cm)
Package 1 Width	4.57 in (11.6 cm)
Package 1 Length	4.53 in (11.5 cm)
Package 1 Weight	4.59 oz (130 g)
Unit Type Of Package 2	BB1
Number Of Units In Package 2	5
Package 2 Height	4.88 in (12.4 cm)
Package 2 Width	4.88 in (12.4 cm)
Package 2 Length	12.91 in (32.8 cm)
Package 2 Weight	26.17 oz (742 g)
Unit Type Of Package 3	CAR
Number Of Units In Package 3	75
Package 3 Height	15.83 in (40.2 cm)
Package 3 Width	15.75 in (40 cm)
Package 3 Length	23.46 in (59.6 cm)
Package 3 Weight	26.35 lb(US) (11.954 kg)

Contractual warranty

Warranty	18 months
----------	-----------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

Well-being performance

✓ Reach Free Of Svhc

✓ Toxic Heavy Metal Free

✓ Mercury Free

✓ Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation

[REACH Declaration](#)

Eu Rohs Directive

Pro-active compliance (Product out of EU RoHS legal scope)

[EU RoHS Declaration](#)

China Rohs Regulation

[China RoHS declaration](#)

Pro-active China RoHS declaration (out of China RoHS legal scope)

Environmental Disclosure

[Product Environmental Profile](#)

Circularity Profile

No need of specific recycling operations