


# Product data sheet

Specifications



ABS box IP66 IK07 RAL7035  
Int.H125W80D65  
Ext.H138W93D72 Transp.cover  
H20

NSYTBS1397T

Product availability: Non-Stock - Not normally stocked in distribution facility

Price\*: 19.99 USD

## Main

Range	Thalassa
Product Name	Thalassa TBS
Device Application	Multi-purpose
Category	Industrial box
Height	5.43 in (138 mm)
Width	3.66 in (93 mm)
Depth	2.83 in (72 mm)
Internal Height	4.92 in (125 mm)
Internal Width	3.15 in (80 mm)
Internal Depth	2.56 in (65 mm)
Enclosure Mounting	Wall mounted
Device Composition	1 body 1 cover 4 cover screw
Quantity Per Set	Set of 2
Body Type	One piece moulded
Type Of Front Cover	Low transparent cover
Cover Fixing	Plastic screws
Lock Type	Captive screw flat outside sealed area
Removable Parts	Cover by captive screws

## Complementary

Material	ABS (acrylonitrile butadiene-styrene)
Color	Gray RAL 7035) Transparent
Standards	IEC 62208
Product Certifications	TÜV
Electrical Insulation Class	Class II
Ip Degree Of Protection	IP66 conforming to NEMA 4.4X
Ik Degree Of Protection	IK07 conforming to IEC 62262

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

<b>Glow Wire Resistance</b>	1202 °F (650 °C) IEC 60695-2-11
<b>Ambient Air Temperature For Storage</b>	5...104 °F (-15...40 °C)
<b>Operating Temperature</b>	-13...140 °F (-25...60 °C)
<b>Net Weight</b>	0.51 lb(US) (0.23 kg)

## Ordering and shipping details

<b>Category</b>	US10ES180033
<b>Discount Schedule</b>	0ES1
<b>Gtin</b>	3606480165429
<b>Returnability</b>	No
<b>Country Of Origin</b>	HU

## Packing Units

<b>Unit Type Of Package 1</b>	PCE
<b>Number Of Units In Package 1</b>	1
<b>Package 1 Height</b>	3.15 in (8 cm)
<b>Package 1 Width</b>	5.71 in (14.5 cm)
<b>Package 1 Length</b>	7.87 in (20 cm)
<b>Package 1 Weight</b>	8.11 oz (230 g)
<b>Unit Type Of Package 2</b>	PAM
<b>Number Of Units In Package 2</b>	1450
<b>Package 2 Height</b>	47.24 in (120 cm)
<b>Package 2 Width</b>	39.37 in (100 cm)
<b>Package 2 Length</b>	84.65 in (215 cm)
<b>Package 2 Weight</b>	835.55 lb(US) (379 kg)

## Contractual warranty

<b>Warranty</b>	18 months
-----------------	-----------

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

## Well-being performance

Reach Free Of Svhc

Toxic Heavy Metal Free

Mercury Free

Rohs Exemption Information Yes

## Certifications & Standards

**Reach Regulation**

[REACH Declaration](#)

**Eu Rohs Directive**

Pro-active compliance (Product out of EU RoHS legal scope)

[EU RoHS Declaration](#)

**China Rohs Regulation**

[China RoHS declaration](#)

Pro-active China RoHS declaration (out of China RoHS legal scope)

**Environmental Disclosure**

[Product Environmental Profile](#)

**Circularity Profile**

No need of specific recycling operations