Product data sheet Characteristics

NSYTBS16128T

ABS box IP66 IK07 RAL7035 Int.H150W105D80 Ext.H164W121D87 Transp.cover H20



Main

Range	Thalassa
Product name	Thalassa TBS
Device Application	Multi-purpose
Category	Industrial box
Height	6.5 in (164 mm)
Width	4.8 in (121 mm)
Depth	3.4 in (87 mm)
Internal height	5.9 in (150 mm)
Internal width	4.1 in (105 mm)
Internal depth	3.1 in (80 mm)
Enclosure mounting	Wall mounted
Device composition	1 body
	1 cover
	4 cover screw
Quantity per Set	Set of 2
Body type	One piece moulded
Type of front cover	Low transparent cover
Cover fixing	Plastic screws
Lock type	Captive screw flat outside sealed area
Removable parts	Cover by captive screws

Complementary

Material	ABS with 45% of post-industrial recycled content	
Color	Gray RAL 7035)	
	Transparent	
Standards	IEC 62208	
Product Certifications	TÜV	
Electrical Insulation Class	Class II	
IP degree of protection	IP66 conforming to NEMA 4.4X	
IK degree of protection	IK07 conforming to IEC 62262	
Glow wire resistance	1202 °F (650 °C) IEC 60695-2-11	
Ambient Air Temperature for Storage	5104 °F (-1540 °C)	
Operating temperature	-13140 °F (-2560 °C)	
Net Weight	0.75 lb(US) (0.34 kg)	

Ordering and shipping details

Category	US10ES180033	
Discount Schedule	0ES1	
GTIN	3606480165436	
Returnability	No	
Country of origin	HU	

Packing Units

3	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.4 in (8.7 cm)
Package 1 Width	4.8 in (12.1 cm)
Package 1 Length	6.5 in (16.4 cm)
Package 1 Weight	12.0 oz (340 g)
Unit Type of Package 2	P12
Number of Units in Package 2	384
Package 2 Height	47.2 in (120 cm)
Package 2 Width	31.5 in (80 cm)
Package 2 Length	53.1 in (135 cm)
Package 2 Weight	341.7 lb(US) (155 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

Warranty	18 months