

# Product data sheet

Specifications



ABS box IP66 IK07 RAL7035  
Int.H175W105D80  
Ext.H192W121D87 Opaque cover  
H20

NSYTBS19128

Product availability: Non-Stock - Not normally stocked in distribution facility

Price\*: 13.84 USD

## Main

Range	Thalassa
Product Name	Thalassa TBS
Device Application	Multi-purpose
Category	Industrial box
Height	7.56 in (192 mm)
Width	4.76 in (121 mm)
Depth	3.43 in (87 mm)
Internal Height	6.89 in (175 mm)
Internal Width	4.13 in (105 mm)
Internal Depth	3.15 in (80 mm)
Enclosure Mounting	Wall mounted
Device Composition	1 body 1 cover 4 cover screw
Quantity Per Set	Set of 2
Body Type	One piece moulded
Type Of Front Cover	Low plain cover
Cover Fixing	Plastic screws
Lock Type	Captive screw flat outside sealed area
Removable Parts	Cover by captive screws

## Complementary

Material	ABS (acrylonitrile butadiene-styrene)
Color	Gray RAL 7035)
Standards	IEC 62208
Product Certifications	TÜV
Electrical Insulation Class	Class II
Ip Degree Of Protection	IP66 conforming to NEMA 4.4X
Ik Degree Of Protection	IK07 conforming to IEC 62262
Glow Wire Resistance	1202 °F (650 °C) IEC 60695-2-11

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

<b>Ambient Air Temperature For Storage</b>	5...104 °F (-15...40 °C)
<b>Operating Temperature</b>	-13...140 °F (-25...60 °C)
<b>Net Weight</b>	0.74 lb(US) (0.335 kg)

## Ordering and shipping details

<b>Category</b>	US10ES180033
<b>Discount Schedule</b>	0ES1
<b>Gtin</b>	3606480165283
<b>Returnability</b>	No
<b>Country Of Origin</b>	HU

## Packing Units

<b>Unit Type Of Package 1</b>	PCE
<b>Number Of Units In Package 1</b>	1
<b>Package 1 Height</b>	3.43 in (8.7 cm)
<b>Package 1 Width</b>	4.76 in (12.1 cm)
<b>Package 1 Length</b>	7.56 in (19.2 cm)
<b>Package 1 Weight</b>	11.82 oz (335 g)
<b>Unit Type Of Package 2</b>	P12
<b>Number Of Units In Package 2</b>	336
<b>Package 2 Height</b>	47.24 in (120 cm)
<b>Package 2 Width</b>	31.50 in (80 cm)
<b>Package 2 Length</b>	53.15 in (135 cm)
<b>Package 2 Weight</b>	306.44 lb(US) (139 kg)

## Contractual warranty

<b>Warranty</b>	18 months
-----------------	-----------

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

## Well-being performance

✓ Reach Free Of Svhc

✓ Toxic Heavy Metal Free

✓ Mercury Free

✓ Rohs Exemption Information Yes

## Certifications & Standards

**Reach Regulation**

[REACH Declaration](#)

**Eu Rohs Directive**

Pro-active compliance (Product out of EU RoHS legal scope)

[EU RoHS Declaration](#)

**China Rohs Regulation**

[China RoHS declaration](#)

Pro-active China RoHS declaration (out of China RoHS legal scope)

**Environmental Disclosure**

[Product Environmental Profile](#)

**Circularity Profile**

No need of specific recycling operations