

# NSYTBS241912H

ABS box IP66 IK07 RAL7035  
Int.H225W175D120 Ext.H241W194D127  
Opaque cover H40



## Main

Range	Thalassa
Product name	Thalassa TBS
Device Application	Multi-purpose
Category	Industrial box
Height	9.5 in (241 mm)
Width	7.6 in (194 mm)
Depth	5.0000000000 in (127 mm)
Internal height	8.9 in (225 mm)
Internal width	6.9 in (175 mm)
Internal depth	4.7 in (120 mm)
Enclosure mounting	Wall mounted
Device composition	1 body 1 cover 4 cover screw
Body type	One piece moulded
Type of front cover	High plain cover
Cover fixing	Plastic screws
Lock type	Captive screw flat outside sealed area
Removable parts	Cover by captive screws

## Complementary

Material	ABS with 45% of post-industrial recycled content
Color	Gray RAL 7035)
Standards	IEC 62208
Product Certifications	TÜV
Electrical Insulation Class	Class II
IP degree of protection	IP66 conforming to NEMA 4.4X
IK degree of protection	IK07 conforming to IEC 62262
Glow wire resistance	1202 °F (650 °C) IEC 60695-2-11
Ambient Air Temperature for Storage	5...104 °F (-15...40 °C)
Operating temperature	-13...140 °F (-25...60 °C)
Net Weight	1.72 lb(US) (0.78 kg)

## Ordering and shipping details

Category	US10ES180033
Discount Schedule	0ES1
GTIN	3606480165351
Returnability	No
Country of origin	HU

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.512 in (14.000 cm)
Package 1 Width	7.874 in (20.000 cm)
Package 1 Length	10.039 in (25.500 cm)
Package 1 Weight	26.843 oz (761.000 g)
Unit Type of Package 2	CAR
Number of Units in Package 2	8
Package 2 Height	15.748 in (40.000 cm)
Package 2 Width	15.748 in (40.000 cm)
Package 2 Length	23.622 in (60.000 cm)
Package 2 Weight	15.106 lb(US) (6.852 kg)
Unit Type of Package 3	P12
Number of Units in Package 3	96
Package 3 Height	53.150 in (135.000 cm)
Package 3 Width	31.496 in (80.000 cm)
Package 3 Length	47.244 in (120.000 cm)
Package 3 Weight	202.825 lb(US) (92.000 kg)

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations

## Contractual warranty

Warranty	18 months
----------	-----------