

Product data sheet

Specifications



ABS box IP66 IK07 RAL7035 Int.H65W65D45 Ext.H74W74D56 Opaque cover H10

NSYTBS775

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 8.24 USD

Main

Range	Thalassa
Product Name	Thalassa TBS
Device Application	Multi-purpose
Category	Industrial box
Height	2.91 in (74 mm)
Width	2.91 in (74 mm)
Depth	2.13 in (54 mm)
Internal Height	2.56 in (65 mm)
Internal Width	2.56 in (65 mm)
Internal Depth	1.85 in (47 mm)
Enclosure Mounting	Wall mounted
Device Composition	1 body 1 cover 4 cover screw
Quantity Per Set	Set of 5
Body Type	One piece moulded
Type Of Front Cover	Low plain cover
Cover Fixing	Metal screws
Lock Type	Captive screw flat outside sealed area
Removable Parts	Cover by captive screws

Complementary

Material	ABS (acrylonitrile butadiene-styrene)
Color	Gray RAL 7035)
Standards	IEC 62208
Product Certifications	TÜV
Electrical Insulation Class	Class II
Ip Degree Of Protection	IP66 conforming to NEMA 4.4X
Ik Degree Of Protection	IK07 conforming to IEC 62262
Glow Wire Resistance	1202 °F (650 °C) IEC 60695-2-11
Ambient Air Temperature For Storage	5...104 °F (-15...40 °C)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Operating Temperature	-13...140 °F (-25...60 °C)
------------------------------	----------------------------

Net Weight	0.15 lb(US) (0.068 kg)
-------------------	------------------------

Ordering and shipping details

Category	US10ES180033
-----------------	--------------

Discount Schedule	0ES1
--------------------------	------

Gtin	3606480165207
-------------	---------------

Returnability	Yes
----------------------	-----

Country Of Origin	HU
--------------------------	----

Packing Units

Unit Type Of Package 1	PCE
-------------------------------	-----

Number Of Units In Package 1	1
-------------------------------------	---

Package 1 Height	0.63 in (1.6 cm)
-------------------------	------------------

Package 1 Width	0.67 in (1.7 cm)
------------------------	------------------

Package 1 Length	2.28 in (5.8 cm)
-------------------------	------------------

Package 1 Weight	2.61 oz (74 g)
-------------------------	----------------

Contractual warranty

Warranty	18 months
-----------------	-----------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

Well-being performance

Reach Free Of Svhc

Toxic Heavy Metal Free

Mercury Free

Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation

[REACH Declaration](#)

Eu Rohs Directive

Pro-active compliance (Product out of EU RoHS legal scope)

[EU RoHS Declaration](#)

China Rohs Regulation

[China RoHS declaration](#)

Pro-active China RoHS declaration (out of China RoHS legal scope)

Environmental Disclosure

[Product Environmental Profile](#)

Circularity Profile

No need of specific recycling operations