NSYTVR15

Vertical uprights height 1500mm. zinc-coated steel. Supply: 2 standard uprights.



Main

Range	Thalassa
Accessory / separate part category	Mounting accessory
Product or Component Type	Technical upright
Device application	Multi-purpose
Enclosure nominal dimensions	- H: 59.06 in (1500 mm)
Mounting Support	Step slide Direct fixing on the rear inserts
Range compatibility	Thalassa Thalassa PLA
Device composition	2 upright
Material	steel

Complementary

Surface Finish	Zinc coated	
Fixing mode	Bosses inserts M8 - rear of enclosure	
Adjustment	Adjustable in depth every 25 mm with caged nuts Adjustable in height every 2.5 mm with quarter-turn nuts	
Height	Nominal: 59.06 in (1500 mm) Real: 54.1 in (1375 mm)	
Width	1.8 in (45 mm)	
Depth	1.3 in (34 mm)	
Thickness	0.08 in (2 mm)	
Cut-out dimensions	11 x 13 mm	

Ordering and shipping details

Category	US10ES180036	
Discount Schedule	0ES1	
GTIN	3606480185076	
Returnability	No	
Country of origin	FR	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.6 in (4.0 cm)
Package 1 Width	2.4 in (6.0 cm)
Package 1 Length	54.3 in (138.0 cm)
Package 1 Weight	9.114 lb(US) (4.134 kg)
Unit Type of Package 2	P2M
Number of Units in Package 2	120
Package 2 Height	19.7 in (50.0 cm)
Package 2 Width	78.7 in (200.0 cm)
Package 2 Length	47.2 in (120.0 cm)
Package 2 Weight	1102.3 lb(US) (500.0 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

	· ·
14/	40 martha
vvarrantv	18 months