Product data sheet Characteristics

NSYTVR7

Vertical uprights height 750mm. zinc-coated steel. Supply: 2 standard uprights.



Main

Range	Thalassa
Accessory / separate part category	Mounting accessory
Product or Component Type	Technical upright
Device application	Multi-purpose
Enclosure nominal dimensions	-
Mounting Support	Direct fixing on the rear inserts Step slide
Range compatibility	Thalassa Thalassa PLA
Device composition	2 upright
Material	steel

Complementary

o o mpromontary		
Surface Finish	Zinc coated	
Fixing mode	Bosses inserts M8 - rear of enclosure	
Adjustment	Adjustable in height every 2.5 mm with quarter-turn nuts	
Height	Nominal: 29.5 in (750 mm) Real: 24.6 in (625 mm)	
Width	1.8 in (45 mm)	
Depth	1.3 in (34 mm)	
Thickness	0.08 in (2 mm)	
Cut-out dimensions	11 x 13 mm	

Ordering and shipping details

Category	US10ES180036
Discount Schedule	0ES1
GTIN	3606480185083
Returnability	No
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	1.4 in (3.5 cm)	
Package 1 Width	2.4 in (6.0 cm)	
Package 1 Length	24.8 in (63.0 cm)	
Package 1 Weight	4.158 lb(US) (1.886 kg)	
Unit Type of Package 2	PAM	
Number of Units in Package 2	60	
Package 2 Height	19.7 in (50.0 cm)	
Package 2 Width	39.4 in (100.0 cm)	
Package 2 Length	47.2 in (120.0 cm)	
Package 2 Weight	277.8 lb(US) (126.0 kg)	

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

	· ·
14/	40 martha
vvarrantv	18 months