



# Active harmonic filter 120 amp 380-480 VAC N2 Enclosure

PCSP120D5N2

Product availability: Stock - Normally stocked in distribution

acility

Price\*: 107,553.33 USD

#### Main

Range Of Product	AccuSine
Product Name	AccuSine PCS+
Product Or Component Type	Active harmonic filter

### Complementary

Network Type	3P
Network Configuration	3 or 4 wires
Network Rated Voltage	380480 V AC
Input Frequency	50/60 Hz +/- 3 Hz auto sensing
Maximum Permissible Voltage	1.1 x Un
Neutral Correction	Not provided
Rms Output Current Rating	120 A
Reactive Power Rating	100 kvar 480 V AC 50/60 Hz
Operating Modes	Harmonic cancellation Power factor correction Mains current balancing
Installation Location	Indoor
Enclosure Mounting	Floor-standing
Protection Type	Circuit breaker protection
Disconnect Type	Door-interlocked with rotary handle
Interrupt Capacity	200 kA
Heat Dissipation	Rear plenum with forced ventilation for high heat flow
Electromagnetic Compatibility	Conducted EMC, class A EN 61000-6-4
Accessibility For Operation	Front
Location Of Connection	Top or bottom

#### **Environment**

Enclosure Degree Of Protection	UL type 2
Environmental Characteristic	Operating 3C2 IEC 60721-3-3
	Operating 3S2 IEC 60721-3-3
	Storage 3C3 IEC 60721-3-3
	Storage 3S3 IEC 60721-3-3
Operating Altitude	<= 3280 84 ft /1000 m) 1 % per 100 m

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Ambient Air Temperature For Operation	32104 °F (040 °C) 32122 °F (050 °C) maximum with current derating of 2 % per °C
Relative Humidity	095 %
Pcba Protection	Conformal coated
Standards	EN 60439-1 CSA C22.2 No 60947-1-07 CSA C22.2 No 14 EN 61000-6-4 UL 60947-1 UL 508
Product Certifications	RCM ABS CE cULus
Ambient Air Temperature For Storage	-4140 °F (-2060 °C)
Net Weight	559.97 lb(US) (254 kg)
Height	82.68 in (2100 mm)
Width	31.50 in (800 mm)
Color	Light gray RAL 7035)
Depth	19.69 in (500 mm)

## Ordering and shipping details

Category	00089-ACTIVE FILTERS
Discount Schedule	DE2C
Gtin	3606480851087
Returnability	No
Country Of Origin	US

## **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	91.77 in (233.1 cm)
Package 1 Width	47.01 in (119.4 cm)
Package 1 Length	47.01 in (119.4 cm)
Package 1 Weight	813.51 lb(US) (369.0 kg)

## **Contractual warranty**

Warranty 18 months

## Sustainability

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

## Well-being performance

trem being perrending	
Toxic Heavy Metal Free	
Mercury Free	
Rohs Exemption Information	Yes
Ex Balan Direction	Consilient
Eu Rohs Directive	Compliant  EU RoHS Declaration
China Rohs Regulation	China RoHS declaration  Product out of China RoHS scope. Substance declaration for your information.
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
California Proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov