



Active harmonic filter - 200 A 380..480 V AC - IP00 enclosure

PCSP200D5IP00

Product availability: Stock - Normally stocked in distribution

facility

Price*: 112,517.33 USD

Main

Range Of Product	AccuSine	
Product Name	AccuSine PCS+	
Product Or Component Type	Active harmonic filter	

Complementary

Network Type	3P
Network Configuration	3 or 4 wires
Network Rated Voltage	380480 V AC
Input Frequency	50/60 Hz +/- 3 Hz auto sensing
Maximum Permissible Voltage	1.1 x Un
Neutral Correction	Not provided
Rms Output Current Rating	200 A
Reactive Power Rating	166 kvar 480 V AC 50/60 Hz
Operating Modes	Harmonic cancellation Power factor correction Mains current balancing
Installation Location	Indoor
Enclosure Mounting	Wall mounted
Protection Type	Without protection
Heat Dissipation	Rear plenum with forced ventilation for high heat flow
Electromagnetic Compatibility	Conducted EMC, class A EN 61000-6-4
Accessibility For Operation	Front
Location Of Connection	Bottom

Environment

Enclosure Degree Of Protection	IP00
Environmental Characteristic	Operating 3C2 IEC 60721-3-3
	Operating 3S2 IEC 60721-3-3 Storage 3C3 IEC 60721-3-3
	Storage 3S3 IEC 60721-3-3
Operating Altitude	<= 3280.84 ft (1000 m) 1 % per 100 m
Ambient Air Temperature For	32104 °F (040 °C)
Operation	32122 °F (050 °C) maximum with current derating of 2 % per °C
Relative Humidity	0 95 %

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Pcba Protection	Conformal coated	
Standards	EN 61000-6-4 CSA C22.2 No 60947-1-07 CSA C22.2 No 14 EN 60439-1 UL 60947-1 UL 508	
Product Certifications	cULus CE DNV-GL RCM ABS	
Ambient Air Temperature For Storage	-4140 °F (-2060 °C)	
Net Weight	385.81 lb(US) (175 kg)	
Height	52.09 in (1323 mm)	
Width	22.91 in (582 mm)	
Color	Light gray RAL 7035)	
Depth	17.24 in (438 mm)	

Ordering and shipping details

Category	00089-ACTIVE FILTERS
Discount Schedule	DE2C
Gtin	3606480851018
Returnability	No
Country Of Origin	US

Packing Units

Unit Type Of Package 1	PCE	
Number Of Units In Package 1	1	
Package 1 Height	27.83 in (70.700 cm)	
Package 1 Width	29.06 in (73.800 cm)	
Package 1 Length	68.58 in (174.200 cm)	
Package 1 Weight	518.09 lb(US) (235.000 kg)	

Contractual warranty

Warranty 18 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Well-being performance

	J ,	
⊘	Reach Free Of Svhc	
9	Toxic Heavy Metal Free	
	Mercury Free	
②	Rohs Exemption Information	Yes
Rea	ch Regulation	REACh Declaration
Eu I	Rohs Directive	Compliant EU RoHS Declaration
Chii	na Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Wee	ee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Cali	fornia Proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov