

# Q4L2250

## QAL MOLDED CASE CIRCUIT BREAKER, 240VAC, 250A, 2P

Product availability : Non-Stock - Not normally stocked in distribution facility



Price\* : 3,171.00 USD



### Main

Product or component type	Circuit breaker
Trip Unit Type	Thermal-magnetic
Rating Code	Q4

### Complementary

Line Rated Current	250 A
Number of Poles	2P
Interrupt Rating	25 kA 120 V AC 25 kA 240 V AC
[Ue] rated operational voltage	240 V AC
Mounting mode	Unit mount
Electrical connection	Lugs load Lugs line
Wire Gauge	AWG 1...600 kcmil aluminium/copper)1 AWG 1...250 kcmil aluminium/copper)2
Terminal Type	AL400LA
Magnetic hold current	1250 A
Magnetic tripping current	2500 A
Maximum Height	11 in (279.40 mm)
Maximum Width	6 in (152.40 mm)
Maximum Depth	5.84 in (148.34 mm)
Tightening torque	371.73 lbf.in (42 N.m) 0.08...0.47 in <sup>2</sup> (50...300 mm <sup>2</sup> ) AWG 1...600 kcmil) 371.73 lbf.in (42 N.m) 0.08...0.19 in <sup>2</sup> (50...120 mm <sup>2</sup> ) AWG 1...250 kcmil)

### Environment

Product certifications	UL Listed
------------------------	-----------

\* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Oct 12, 2020

CSA  
IEC

Ambient air temperature for operation 104 °F (40 °C)

### Ordering and shipping details

Category 00933 - Q4L BREAKER & SWITCH

Discount Schedule DE2

GTIN 00785901649212

Returnability No

Country of origin MX

### Offer Sustainability

Sustainable offer status Green Premium product

California proposition 65 WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause Birth Defects or other reproductive harm. For more information go to [www.p65warnings.ca.gov](http://www.p65warnings.ca.gov)

EU RoHS Directive Compliant  
[EU RoHS Declaration](#)

Mercury free Yes

RoHS exemption information Yes

China RoHS Regulation [China RoHS declaration](#)  
Product out of China RoHS scope. Substance declaration for your information.

Environmental Disclosure [Product Environmental Profile](#)

### Contractual warranty

Warranty 18 months