

QBP22175TM

PowerPact Q - molded case circuit breaker - 2-pole - 10 kA - 240 V - 175 A

Product availability : Stock - Normally stocked in distribution facility



Price* : 474.00 USD



Main

| | |
|---------------------------|--|
| Product or component type | Circuit breaker |
| Range of product | PowerPact Q |
| Trip unit technology | Thermal-magnetic |
| Provided equipment | Lug OFF end Stud with nut and washer ON end |

Complementary

| | |
|--------------------------------|---|
| Line Rated Current | 175 A |
| [Ue] rated operational voltage | 240 V AC |
| Number of poles | 2 |
| Breaking capacity | 10 kA 240 V AC |
| Continuous current rating | 80 % |
| Breaking capacity code | B |
| Mounting mode | Unit mount |
| Electrical connection | Lugs load Terminal nut line AWG 4...300 kcmil aluminium/copper |
| Magnetic hold current | 1200 A |
| Magnetic tripping current | 2400 A |
| Maximum Height | 6.47 in (164.34 mm) |
| Maximum Width | 4.5 in (114.30 mm) |
| Maximum Depth | 3.93 in (99.82 mm) |
| Tightening torque | 247.82 lbf.in (28 N.m) 0.04...0.23 in ² (25...150 mm ²) AWG 4...300 kcmil) |

Environment

| | |
|------------------------|-----|
| Product certifications | CSA |
|------------------------|-----|

* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

UL Listed
IEC

Ordering and shipping details

| | |
|-------------------|-----------------------------------|
| Category | 00024 - Q2 & QE METERING BREAKERS |
| Discount Schedule | DE2A |
| GTIN | 00785901689850 |
| Returnability | Yes |
| Country of origin | MX |

Offer Sustainability

| | |
|-----------------------------|--|
| Sustainable offer status | Green Premium product |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information. |
| Environmental Disclosure | Product Environmental Profile |
| PVC free | Yes |
| Halogen content performance | Halogen free product |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|