Product data sheet

Specifications



Green



Load center, QO, 1 phase, 2 spaces, 4 circuits, 60A fixed main lugs, NEMA3R, gnd bar, nonmetalic

QO24L60NRNM

Product availability: Stock - Normally stocked in distribution facility

Price*: 102.00 USD

Main

Product Type	Load Center
Range Of Product	QO
Load Center Type	Fixed Mains (lugs)

Complementary

Complementary	
Current Rating	60 A
Interrupt Rating	10 kA
Number Of Spaces	2
Maximum Number Of Single Pole Circuits	4
Maximum Number Of Tandem Breakers	2
Number Of Phases	1 phase
Enclosure Rating	NEMA 3R outdoor
Breaker Compatibility	Circuit breaker QO 1P Circuit breaker QO 2P
Product Certifications	UL Listed
Wiring Configuration	3-wire
Electrical Connection	Lugs
Wire Size	AWG 14AWG 4 aluminium/copper
Busbar Material	Tin plated aluminium: busbar
Voltage Rating	120/240 V AC
Ambient Air Temperature For Operation	23 °F (-5 °C) 104 °F (40 °C)
Tightening Torque	Main lugs 35 lb.in, AWG 14AWG 10, aluminium/copper Main lugs 45 lb.in, AWG 3, aluminium/copper Main lugs 40 lb.in, AWG 8AWG 4, aluminium/copper Main lugs 35 lb.in, AWG 12AWG10, aluminium/copper
Box Number	1NM
Ground Bar	Grounding bar (factory installed)
Enclosure Material	Non-metallic
Enclosure Type	Enclosure
Height	8.78 in (223 mm)

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Width	6.54 in (166 mm)
Depth	2.87 in (73 mm)

Ordering and shipping details

Category	00101-QO 1PH LC,2-8CKT,NEMA 1,3R	
Discount Schedule	chedule DE3A	
Gtin	785901328025	
Returnability	Yes	
Country Of Origin	MX	

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	4.00 in (10.16 cm)
Package 1 Width	5.80 in (14.732 cm)
Package 1 Length	9.60 in (24.384 cm)
Package 1 Weight	22.89 oz (649.0 g)
Unit Type Of Package 2	CAR
Number Of Units In Package 2	10
Package 2 Height	10.20 in (25.908 cm)
Package 2 Width	13.00 in (33.02 cm)
Package 2 Length	20.70 in (52.578 cm)
Package 2 Weight	15.36 lb(US) (6.967 kg)
Unit Type Of Package 3	PAL
Number Of Units In Package 3	240
Package 3 Height	40.00 in (101.6 cm)
Package 3 Width	40.00 in (101.6 cm)
Package 3 Length	48.00 in (121.92 cm)
Package 3 Weight	379.00 lb(US) (171.911 kg)

Contractual warranty

Warranty

18 months

Sustainability Screen

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Reach Free Of Svhc

Toxic Heavy Metal Free	
Mercury Free	
Rohs Exemption Information	Yes


Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
	Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
California Proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Product data sheet

Technical illustration

Dimensions




ALL DIMENSIONS ARE APPROXIMATE. REFER TO TECHNICAL DRAWINGS AND DOCUMENTATION WHEN MOUNTING, ALLOW 1.50IN / 38MM CLEARANCE ON HINGE SIDE FOR DOOR TO OPEN.

Wiring diagram

Product data sheet QO24L60NRNM

Technical illustration



QO24L60NRNM

Dec 29, 2023