

# Product data sheet

## Characteristics

# QOM2225VHL

Main breaker, QO, 225A, 2 pole, 120/240 VAC, 22 kA, bolt on mount

Product availability : Non-Stock - Not normally stocked in distribution facility



Price\* : 575.00 USD



### Main

Product	Circuit breaker
Range	QO
Current Rating	225 A
Voltage Rating	120/240 V AC
Mounting Type	Bolt-on
Number of Poles	2P
Circuit Breaker Type	Standard
Ratings	Primary main breaker
Electrical Connection	Lugs
Frame Size	QOM2

### Complementary

Interrupt Rating	22 kA 120/240 V AC 50/60 Hz
Wire Size	AWG 4...250 kcmil copper or aluminium
Tightening torque	53.10 lbf.in (6 N.m) 0.01...0.10 in <sup>2</sup> (4...65 mm <sup>2</sup> ) AWG 12...AWG 2/0
Maximum Height	5.6 in (142.24 mm)
Maximum Depth	3.6 in (91.44 mm)
Maximum Width	5.07 in (128.78 mm)
Load center type	Main breaker
Number of Phases	1 phase
For Use With	QO load center

### Environment

Certifications	UL Listed CSA
----------------	------------------

\* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Oct 1, 2020



Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Ambient Rating	104 °F (40 °C)
----------------	----------------

### Ordering and shipping details

Category	00157 - CANADIAN QO CIRCUIT BKRS
Discount Schedule	DE2A
GTIN	00785901372653
Nbr. of units in pkg.	1
Package weight(Lbs)	2.6 lb(US) (1.18 kg)
Returnability	No
Country of origin	MX

### Packing Units

Package 1 Height	4.50 in (11.430 cm)
Package 1 width	5.50 in (13.970 cm)
Package 1 Length	6.50 in (16.510 cm)

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

### Contractual warranty

Warranty	18 months
----------	-----------