

# RJF36200U44A

## POWERPACT R-FRAME, MOLDED CASE CIRCUIT BREAKER, 600V, 2000A, 3P, 25kA

Product availability : Stock - Normally stocked in distribution facility



Price\* : 28,553.00 USD



### Main

Product or component type	Circuit breaker
Range of product	PowerPact R
Current sensor rating range	2000 A
Trip unit technology	Electronic, ammeter, Micrologic 6.0 A, LSIG

### Complementary

[Ie] rated operational current	2000 A
[Ue] rated operational voltage	600 V AC
Mounting mode	Unit mount
Poles description	3P
Breaking capacity	100 kA 240 V AC 65 kA 480 V AC 25 kA 600 V AC
Breaking capacity code	J
Continuous current rating	80 %
Electrical connection	Busbar connection line Busbar connection load
Maximum Height	16.24 in (412.50 mm)
Maximum Width	16.53 in (419.86 mm)
Maximum Depth	14.49 in (368.05 mm)
Tightening torque	601.85 lbf.in (68 N.m) 0.08...0.62 in <sup>2</sup> (50...400 mm <sup>2</sup> ) AWG 1/0...750 kcmil 601.85 lbf.in (68 N.m) 0.08...0.23 in <sup>2</sup> (50...150 mm <sup>2</sup> ) AWG 1/0...300 kcmil

### Environment

Product certifications	CSA UL Listed
------------------------	------------------

\* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Oct 12, 2020

### Ordering and shipping details

Category	01245 - RG,H,J,K,L,N UNIT MT BREAKERS
Discount Schedule	DE2
GTIN	00785901280866
Returnability	Yes
Country of origin	US

### Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DIDP and DINP which is known to the State of California to cause Carcinogen and Reproductive harm. For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>
PVC free	Yes
Halogen content performance	Halogen free plastic parts product

### Contractual warranty

Warranty	18 months
----------	-----------