

Product data sheet

Specifications



standard Network Interface Module STB - DeviceNet - 125..500 kbit/s

STBNDN2212

Product availability: Stock - Normally stocked in distribution facility

Main

Range of Product	Modicon STB distributed I/O solution
Product or Component Type	Standard Network Interface Module
Integrated connection type	DeviceNet Open DeviceNet Vendors Assoc 5-way male 1 twisted pair network) DeviceNet Open DeviceNet Vendors Assoc HE-13 RS232 port) DeviceNet Open DeviceNet Vendors Assoc 8-way female RS232 port)
Number of segments	1 primary, maximum 6 extensions
Number of server device(s)	64
Transmission rate	125...500 kbit/s 0.0000000000...3937.008 ft (0...1200 m)

Complementary

Number of addressable I/O module	0...32 per island
Communication Service	Island Bus Object (class ID101) DeviceNet Object (class ID3) Connection Object (class ID5)
[Us] rated supply voltage	24 V DC
power supply type	SELV
Maximum supply current	700 A
Supply voltage limits	19.2...30 V
Input current	430 mA supply circuit
Nominal output current	0.575 A 140...158 °F (60...70 °C) 1.2 A
Maximum output impedance	0.05 Ohm 100000 kHz
Output voltage	5.25 V DC +/- 0.21 %)logic bus
marking	CE
Overvoltage category	II
Status LED	1 LED (Green) island state (RUN) 1 LED (Green) MNSG 1 LED (Green) MNSR 1 LED (Green) power supply (PWR) 1 LED (Red) module error (ERR) 1 LED (Yellow) test mode
Depth	2.8 in (70 mm)
Height	1.6 in (40 mm)
Width	5.05 in (128.3 mm)

Environment

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Electromagnetic compatibility	Immunity to electromagnetic interference IEC 61131-2
Product Certifications	FM Class 1 Division 2 CSA UL ATEX Cat 3G C-tick
Pollution degree	2 IEC 60664-1
Operating altitude	<= 6561.68 ft (2000 m)
IP degree of protection	IP20 conforming to IEC 61131-2 class 1
Ambient air temperature for operation	32...140 °F (0...60 °C) without derating -13...158 °F (-25...70 °C) with derating factor)
Ambient Air Temperature for Storage	-40...185 °F (-40...85 °C)
Relative humidity	95 % 140 °F (60 °C) without condensation
Vibration resistance	3 gn 58...150 Hz 35 x 7.5 mm symmetrical DIN rail 5 gn 58...150 Hz 35 x 15 mm symmetrical DIN rail +/-0.35 mm 10...58 Hz
Shock resistance	30 gn 11 ms IEC 88 reference 2-27

Ordering and shipping details

Category	US1PC3218215
Discount Schedule	PC32
GTIN	3595862055123
Returnability	No
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.73 in (4.400 cm)
Package 1 Width	2.83 in (7.200 cm)
Package 1 Length	5.12 in (13.000 cm)
Package 1 Weight	6.596 oz (187.000 g)
Unit Type of Package 2	S02
Number of Units in Package 2	30
Package 2 Height	5.91 in (15.000 cm)
Package 2 Width	11.81 in (30.000 cm)
Package 2 Length	15.75 in (40.000 cm)
Package 2 Weight	13.054 lb(US) (5.921 kg)

Contractual warranty

Warranty	18 months
-----------------	-----------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[How we assess product sustainability >](#)



Transparency

Well-being performance

✓ Mercury Free

✓ Rohs Exemption Information [Yes](#)

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Pro-active compliance (Product out of EU RoHS legal scope)

China Rohs Regulation [China RoHS declaration](#)

Environmental Disclosure [Product Environmental Profile](#)

Weee The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

California Proposition 65 WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Scip Number F760fd97-89c1-4651-a374-9b8eff254b6a

Dimensions Drawings

Dimensions

