Product data sheet Characteristics

TM5ACBM3FS

Safety coded bus base - 24V DC - internal I/O red - quantity 1

Product availability: Stock - Normally stocked in distribution facility



Price*: 31.00 USD



Main

| Modicon TM5 |
|---------------------------|
| Bus base |
| Communication accessories |
| TM5 safety I/O modules |
| 1 |
| |

Complementary

| o o mpromornary | | <u> </u> |
|---------------------------|--------------------------------|-----------|
| Range compatibility | Modicon M258 Modicon LMC058 | eterminir |
| Color | Red | ford |
| [Us] rated supply voltage | 24 V DC | pesn |
| Power consumption in W | 0.13 W | o o |

Environment

| EE | | |
|--|--|--|
| 4 | | |
| 6.5.4 | | |
| | | |
| | | |
| Main | | |
| Range of product | Modicon TM5 | |
| Accessory / separate part type | Bus base | |
| Accessory / separate part category | Communication accessories | |
| Product compatibility | TM5 safety I/O modules | |
| Sale per indivisible quantity | 1 | |
| | | |
| Complementary | | |
| Range compatibility | Modicon M258 | |
| | Modicon LMC058 | |
| Color | Red | |
| [Us] rated supply voltage | 24 V DC | |
| Power consumption in W | 0.13 W | |
| | | |
| Environment | | |
| Constitution and Activities and Acti | CE | |
| Product certifications | CULus | |
| IP degree of protection | IP20 | |
| Ambient air temperature for operation | 32131 °F (055 °C) horizontal 32122 °F (050 °C) vertical | |
| Ambient air temperature for storage | -13158 °F (-2570 °C) | |
| Relative humidity | 595 % without condensation or dripping water | |
| Operating altitude | 06561.68 ft (02000 m) | |
| | | |
| Ordering and shipping details | | |
| Category | 18360 - PACDRIVE3 SAFETY | |
| * Price is "List Price" and may be subject to a trade dis | scount – check with your local distributor or retailer for actual price. | |
| 24.0.2020 | | |

Ordering and shipping details

| Category | 18360 - PACDRIVE3 SAFETY | |
|----------|--------------------------|--|
| | | |

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Oct 9, 2020



| Discount Schedule | PC52 |
|-----------------------|--------------------|
| GTIN | 00785901946120 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 1 lb(US) (0.45 kg) |
| Returnability | Yes |
| Country of origin | AT |

Packing Units

| Unit Type of Package 1 | PCE |
|------------------------------|----------------------|
| Package 1 Height | 1.18 in (3 cm) |
| Package 1 width | 2.36 in (6 cm) |
| Package 1 Length | 4.33 in (11 cm) |
| Unit Type of Package 2 | S02 |
| Number of Units in Package 2 | 50 |
| Package 2 Weight | 7.50 lb(US) (3.4 kg) |
| Package 2 Height | 5.91 in (15 cm) |
| Package 2 width | 11.81 in (30 cm) |
| Package 2 Length | 15.75 in (40 cm) |

Offer Sustainability

| WEEE | The product must be disposed on European Union markets following specific waste collection and |
|----------------------------|---|
| Circularity Profile | End of Life Information |
| Environmental Disclosure | Product Environmental Profile |
| China RoHS Regulation | China RoHS declaration |
| RoHS exemption information | Yes |
| Mercury free | Yes |
| Toxic heavy metal free | Yes |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| REACh free of SVHC | Yes |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds which i known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov |
| Sustainable offer status | Green Premium product |
| 0 | One of Department of the Control of |

Contractual warranty

| The state of the s | |
|--|-----------|
| Warranty | 18 months |