Product data sheet Characteristics

TMC4AI2 cartridge M241 - 2 analog current inputs

Product availability: Stock - Normally stocked in distribution facility



Price*: 149.00 USD



Main

Modicon M241
Analogue input cartridge
Modicon M241C
2
_

Complementary

Main		
Range of product	Modicon M241	
Product or component type	Analogue input cartridge	
Product compatibility	Modicon M241C	
Analogue input number	2	
Complementary		
Analogue input type	current 420 mA current 020 mA voltage 010 V	
Analogue input resolution	16 bits	
LSB value	1 mV voltage 2 μA current	
Sampling duration	10 ms	
Absolute accuracy error	+/- 0.2 % of full scale 77 °F (25 °C)	
Temperature drift	+/- 0.006 %FS/°C	
Repeat accuracy	+/- 0.2 %FS	
Non-linearity	+/- 0.05 %FS	
Cross talk	80 dB	
Type of cable	Twisted shielded pairs cable	
Electrical connection	1 x 1.5 mm² 1 spring terminal block pitch 3.81 mm for inputs and supply	
Maximum cable distance between devices	Twisted shielded pairs cable <98.43 ft (30 m) input	
Insulation	Between input and internal logic 500 V DC Non-insulated between inputs	
Supply voltage limits	20.428.8 V	
ocal signalling	PWR 1 LED green)	
Maximum Height	1.97 in (50 mm)	

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.







Maximum Depth	0.83 in (21 mm)
Maximum Width	1.34 in (34 mm)
Net Weight	0.12 lb(US) (0.055 kg)
Permissible continuous overload	40 mA current 30 V voltage
Input impedance	<= 250 Ohm current >= 1 MOhm voltage

Environment

Ordering and shipping details

Category	22533 - M2XX PLC & ACCESSORIES
Discount Schedule	MSX
GTIN	00785901312505
Nbr. of units in pkg.	1
Package weight(Lbs)	0.15 lb(US) (0.07 kg)
Returnability	Yes
Country of origin	ID

Packing Units

Package 1 Height	2.76 in (70.000 mm)
Package 1 width	1.38 in (35.000 mm)
Package 1 Length	1.18 in (30.000 mm)

Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
PVC free	Yes