# Product data sheet Characteristics

# TMC4AQ2 cartridge M241 - 2 analog outputs

Product availability: Stock - Normally stocked in distribution facility



Price\*: 169.00 USD



#### Main

Range of product	Modicon M241
Product or component type	Analogue output cartridge
Product compatibility	Modicon M241C

#### Complementary

cartridge
~
~
~
~
A
ltage urrent
rent ge
oller cycle time
scale 77 °F (25 °C)
pairs cable
ring terminal block pitch 3.81 mm for outputs and supply
pairs cable <98.43 ft (30 m) input
and internal logic 500 V DC
b

<sup>\*</sup> Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.



Oct 10, 2020



#### Non-insulated between outputs

Supply voltage limits	20.428.8 V
Local signalling	PWR 1 LED green)
Maximum Height	1.97 in (50 mm)
Maximum Depth	0.83 in (21 mm)
Maximum Width	1.34 in (34 mm)
Net Weight	0.12 lb(US) (0.055 kg)

## **Environment**

Immunity to microbrooks	10 mg	
Immunity to microbreaks	10 ms	
the second secon		

## Ordering and shipping details

and an appropriate the second	
Category	22533 - M2XX PLC & ACCESSORIES
Discount Schedule	MSX
GTIN	00785901329442
Nbr. of units in pkg.	1
Package weight(Lbs)	0.14 lb(US) (0.06 kg)
Returnability	Yes
Country of origin	ID

# Packing Units

Package 1 Height	2.76 in (70.000 mm)	7
Package 1 width	1.38 in (35.000 mm)	
Package 1 Length	1.18 in (30.000 mm)	

## Offer Sustainability

Sustainable offer status	Green Premium product		
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration		
Mercury free	Yes		
RoHS exemption information	Yes		
China RoHS Regulation	China RoHS declaration		
Environmental Disclosure	Product Environmental Profile		
Circularity Profile	End of Life Information		
PVC free	Yes		