Product data sheet Characteristics

TMC4HOIS01

cartridge M241 - hoisting 1 analog input

Product availability: Non-Stock - Not normally stocked in distribution facility



Price*: 169.00 USD



Main

Range of product	Modicon M241	
Product or component type	Analogue input cartridge	
Product specific application	Hoisting applications	
Product compatibility	Modicon M241C	-
Analogue input number	2	

Complementary

PWR		
Main		
Range of product	Modicon M241	
Product or component type	Analogue input cartridge	
Product specific application	Hoisting applications	
Product compatibility	Modicon M241C	
Analogue input number	2	
Complementary		
Analogue input type	current 420 mA current 020 mA voltage 010 V	
Analogue input resolution	16 bits	
LSB value	1 mV voltage 010 V 2 μA current 020 mA 2 μA current 420 mA	
Sampling duration	10 ms	
Absolute accuracy error	+/- 0.2 % of full scale 77 °F (25 °C)	
Temperature drift	+/- 0.006 %FS/°C	
Repeat accuracy	+/- 0.2 %FS	
Non-linearity	+/- 0.05 %FS	
Cross talk	80 dB	
Type of cable	Twisted shielded pairs cable	
Electrical connection	1 x 1.5 mm ² 1 spring terminal block pitch 3.81 mm for inputs and supply	
Maximum cable distance between devices	Twisted shielded pairs cable <98.43 ft (30 m) input	
Insulation	Between input and internal logic 500 V DC Non-insulated between inputs	
Supply voltage limits	20.428.8 V	
Local signalling	PWR 1 LED green)	

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.





1.97 in (50 mm)
0.83 in (21 mm)
1.34 in (34 mm)
0.12 lb(US) (0.055 kg)
40 mA current 30 V voltage
<= 250 Ohm current >= 1 MOhm voltage

Environment

Immunity to microbreaks	10 ms		

Ordering and shipping details

Category	22533 - M2XX PLC & ACCESSORIES
Discount Schedule	MSX
GTIN	00785901474425
Nbr. of units in pkg.	1
Package weight(Lbs)	0.14 lb(US) (0.06 kg)
Returnability	No
Country of origin	ID

Packing Units

Package 1 Height	2.76 in (70.000 mm)	
Package 1 width	1.38 in (35.000 mm)	
Package 1 Length	1.18 in (30.000 mm)	

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	End of Life Information	
PVC free	Yes	