Product data sheet Characteristics

XGSZ24

RS232/RS485 interface, Radio frequency identification XG, RS 232/RS 485 line adaptor, for XGS K, XGS D





Main	
Range of product	Telemecanique Radio frequency identification XG
Accessory / separate part destination	XGSD
	XGSK
	XGCS
Product or component type	RS232/RS485 interface
Accessory / separate part type	RS232C/RS485 line adaptor

Complementary

Communication port converter	RS232C/RS485 no modem signals	
Connection element	RS232/RS485 interface	
Current consumption	20 mA	
[le] rated operational current DC	20 mA	
Mounting support	35 mm symmetrical DIN rail	
Product mounting	35 mm symmetrical DIN rail	
Net weight	0.105 Kg	
	0.1 kg	
[Us] rated supply voltage	1830 V DC	
	24 V DC	
Supply voltage limits	2030 V	
Transmission rate	<= 19200 bit/s	
	19200 bauds	
Electrical connection	Screw connectors	

Packing Units

3		
Unit Type of Package 1	PCE	100
Number of Units in Package 1	1	
Package 1 Weight	109 g	
Package 1 Height	5 cm	
Package 1 width	6.5 cm	
Package 1 Length	13 cm	179
Unit Type of Package 2	S02	
Number of Units in Package 2	28	
Package 2 Weight	3.422 kg	
Package 2 Height	15 cm	
Package 2 width	30 cm	
Package 2 Length	40 cm	- 10
	· · · · · · · · · · · · · · · · · · ·	

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	₫ Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Contractual warranty

Warranty	18 months

