Product data sheet Characteristics

XVS10GMW

Multi sound siren, white, 0...106 dB, 2 tones, 120 **VAC**

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 150.00 USD



Main

Range of product	Harmony XVS
Product or component type	Siren
Device short name	XVS
Color	White
Signalling type	2 tones siren
[Us] rated supply voltage	120 V AC
Noise level	106 dB continuous or intermittent tone)1 m

Complementary

Main		
Range of product	Harmony XVS	
Product or component type	Siren	
Device short name	XVS	
Color	White	
Signalling type	2 tones siren	
[Us] rated supply voltage	120 V AC	
Noise level	106 dB continuous or intermittent tone)1 m	
Complementary		
Material	PC body	
Net Weight	2.20 lb(US) (1 kg)	
Marking	CE	
[Uimp] rated impulse withstand voltage	4 kV	
Current consumption	80 mA 120 V	
Clamping connection capacity	<= 1 x 1.5 mm²	
Electrical connection	Cable 0.260.33 in (6.58.5 mm)	
Maximum Width	4.49 in (114 mm)	
Maximum Height	4.49 in (114 mm)	
Maximum Depth	6.03 in (153.2 mm)	
Environment		
Standards	EN/IEC 60947-1 EN/IEC 60947-5-1	
Protective treatment	TC	
Ambient air temperature for storage	-31158 °F (-3570 °C)	
Ambient air temperature for operation	-22122 °F (-3050 °C)	
Electrical shock protection class	Class II EN/IEC 61140	
IP degree of protection	IP53	

Environment

LITTIONICH		ñ
Standards	EN/IEC 60947-1 EN/IEC 60947-5-1	net de de
Protective treatment	TC	100
Ambient air temperature for storage	-31158 °F (-3570 °C)	
Ambient air temperature for operation	-22122 °F (-3050 °C)	
Electrical shock protection class	Class II EN/IEC 61140	
IP degree of protection	IP53	- S

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.







Ordering and shipping details

Category	22617 - XVC TOWER LIGHTS
Discount Schedule	XV
GTIN	00785901944768
Returnability	No
Country of origin	ID

Offer Sustainability

- · · · · · · · · · · · · · · · · · · ·		
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	End of Life Information	
	<u> </u>	

Contractual warranty

Warranty	18 months

Product data sheet Dimensions Drawings

XVS10GMW

Siren

Dimensions



