

# Product data sheet

Specifications



Head for pilot light, Harmony XAC,  
for incandescent bulb, plastic,  
green cap, 22mm

ZA2BV03

Product availability: Stock - Normally stocked in distribution facility

**Price\*: 9.60 USD**

## Main

Range Of Product	Harmony
Product Or Component Type	Head for pilot light
Product Specific Application	For incandescent bulb
Cap/Operator Or Lens Colour	Green

## Complementary

Mechanical Durability	1000000 cycles
Net Weight	0.03 lb(US) (0.015 kg)
Compatibility Code	ZA2B

## Environment

Standards	CSA C22.2 No 14 EN/IEC 60947-5-1
Protective Treatment	TH
Ambient Air Temperature For Operation	-13...131 °F (-25...55 °C)
Ambient Air Temperature For Storage	-40...158 °F (-40...70 °C)
Vibration Resistance	15 gn 10...500 Hz)IEC 60068-2-6
Shock Resistance	100 gn IEC 60068-2-27
Electrical Shock Protection Class	Class II IEC 61140
Overvoltage Category	Class II IEC 61140
Ip Degree Of Protection	IP65 conforming to IEC 60529
Ik Degree Of Protection	IK08 EN 50102

## Ordering and shipping details

Category	22460-PUSHBUTTONS 22MM (PLASTIC)
Discount Schedule	CS2
Gtin	3389110645361
Returnability	Yes
Country Of Origin	FR

## Packing Units

Unit Type Of Package 1	PCE
------------------------	-----

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

<b>Number Of Units In Package 1</b>	1
<b>Package 1 Height</b>	1.38 in (3.5 cm)
<b>Package 1 Width</b>	1.57 in (4.0 cm)
<b>Package 1 Length</b>	1.57 in (4.0 cm)
<b>Package 1 Weight</b>	0.53 oz (15.0 g)
<b>Unit Type Of Package 2</b>	BB1
<b>Number Of Units In Package 2</b>	10
<b>Package 2 Height</b>	1.97 in (5.0 cm)
<b>Package 2 Width</b>	6.69 in (17.0 cm)
<b>Package 2 Length</b>	5.91 in (15.0 cm)
<b>Package 2 Weight</b>	5.36 oz (152.0 g)
<b>Unit Type Of Package 3</b>	S01
<b>Number Of Units In Package 3</b>	100
<b>Package 3 Height</b>	5.91 in (15.0 cm)
<b>Package 3 Width</b>	5.91 in (15.0 cm)
<b>Package 3 Length</b>	15.75 in (40.0 cm)
<b>Package 3 Weight</b>	3.76 lb(US) (1.705 kg)

## Contractual warranty

<b>Warranty</b>	18 months
-----------------	-----------

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

## Well-being performance

Reach Free Of Svhc

Toxic Heavy Metal Free

Mercury Free

Rohs Exemption Information Yes

## Certifications & Standards

**Reach Regulation**

[REACH Declaration](#)

**Eu Rohs Directive**

Pro-active compliance (Product out of EU RoHS legal scope)

[EU RoHS Declaration](#)

**China Rohs Regulation**

[China RoHS declaration](#)

**Environmental Disclosure**

[Product Environmental Profile](#)

**Circularity Profile**

[End of Life Information](#)

**California Proposition 65**

WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)