



Price* : 36,111.00 USD



Main

Product or component type	Circuit breaker
Range of product	PowerPact R
Current sensor rating range	1200 A
Trip unit technology	Electronic, standard, Micrologic 3.0, LI

Complementary

[Ie] rated operational current	1200 A
[Ue] rated operational voltage	600 V AC
Mounting mode	I-Line
Poles description	3P
Breaking capacity	100 kA 240 V AC 65 kA 480 V AC 25 kA 600 V AC
Breaking capacity code	J
Continuous current rating	100 %
Electrical connection	I-Line connection line Lugs load
AWG gauge	AWG 3/0...600 kcmil aluminium/copper
Maximum Height	13.38 in (339.85 mm)
Maximum Width	14.96 in (379.98 mm)
Maximum Depth	13.78 in (350.01 mm)
Tightening torque	247.82 lbf.in (28 N.m) 0.15...0.37 in ² (95...240 mm ²) AWG 4/0...500 kcmil)

Environment

Product certifications	UL Listed CSA IEC
------------------------	-------------------------

* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Ordering and shipping details

Category	01240-RG,H,J,K,L,N I-LINE BREAKERS
Discount Schedule	DE2
GTIN	00785901788836
Returnability	Yes
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
PVC free	Yes
Halogen content performance	Halogen free plastic parts product

Contractual warranty

Warranty	18 months
----------	-----------