



Price\* : 36,599.00 USD



## Main

Product or component type	Circuit breaker
Range of product	PowerPact R
Current sensor rating range	1200 A
Trip unit technology	Electronic, standard, Micrologic 5.0, LSI

## Complementary

[Ie] rated operational current	1200 A
[Ue] rated operational voltage	600 V AC
Mounting mode	I-Line
Poles description	3P
Breaking capacity	100 kA 240 V AC 65 kA 480 V AC 25 kA 600 V AC
Breaking capacity code	J
Continuous current rating	100 %
Electrical connection	I-Line connection line Lugs load
AWG gauge	AWG 3/0...600 kcmil aluminium/copper
Maximum Height	13.38 in (339.85 mm)
Maximum Width	14.96 in (379.98 mm)
Maximum Depth	13.78 in (350.01 mm)
Tightening torque	247.82 lbf.in (28 N.m) 0.15...0.37 in <sup>2</sup> (95...240 mm <sup>2</sup> ) AWG 4/0...500 kcmil)

## Environment

Product certifications	CSA UL Listed IEC
------------------------	-------------------------

\* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Oct 12, 2020

### Ordering and shipping details

Category	01240-RG,H,J,K,L,N I-LINE BREAKERS
Discount Schedule	DE2
GTIN	00785901839163
Returnability	Yes
Country of origin	US

### Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>
PVC free	Yes
Halogen content performance	Halogen free plastic parts product

### Contractual warranty

Warranty	18 months
----------	-----------