Product data sheet Characteristics

RJA36120CU44A

Circuit breaker, PowerPact R, I-Line, Micrologic 6.0A, 1200A, 3 pole, 25 kA@600 VAC, phase ABC

Product availability: Non-Stock - Not normally stocked in distribution facility





Price*: 40,829.00 USD



Main

Product or component type	Circuit breaker	
Range of product	PowerPact R	
Current sensor rating range	1200 A	
Trip unit technology	Electronic, ammeter, Micrologic 6.0 A, LSIG	

Complementary

the street of th		
[le] rated operational current	1200 A	
[Ue] rated operational voltage	600 V AC	
Mounting mode	I-Line	
Poles description	3P	
Breaking capacity	100 kA 240 V AC 65 kA 480 V AC 25 kA 600 V AC	
Breaking capacity code	J	
Continuous current rating	100 %	
Electrical connection	I-Line connection line Lugs load	
AWG gauge	AWG 3/0600 kcmil aluminium/copper	
Maximum Height	13.38 in (339.85 mm)	
Maximum Width	14.96 in (379.98 mm)	
Maximum Depth	13.78 in (350.01 mm)	
Tightening torque	247.82 lbf.in (28 N.m) 0.150.37 in² (95240 mm²) AWG 4/0500 kcmil)	

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.





Environment

Product certifications	UL Listed	
	IEC	
	CSA	

Ordering and shipping details

Category	01240 - RG,H,J,K,L,N I-LINE BREAKERS	
Discount Schedule	DE2	
GTIN	00785901566526	
Returnability	No	
Country of origin	US	

Offer Sustainability

Green Premium product	
Compliant EU RoHS Declaration	
Yes	
Yes	
China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.	
Product Environmental Profile	
End of Life Information	
Yes	
Halogen free plastic parts product	

Contractual warranty

Warranty	18 months
----------	-----------