SIEMENS

Data sheet US2:HF362



Siemens Low Voltage Circuit Protection Heavy Duty Safety Switches. Type: ENCLOSED, SAFETY SWITCH Std: UL V. Rating: 600V A. Rating: 60A Wattage: 3W No. Of Poles: 3P F. Rating: 60Hz Action: SINGLE THROW Material: STEEL Enclosure: TYPE 1. 2-3 point mounting holes. O. Cycles: 10000 O. Temperature: (-20F-120F) AMBIENT TEMPERATURE Environmental Conditions: INDOOR

| installation location | INDOOR |
|--|-----------------------------|
| principle of operation of the actuating element | SINGLE THROW |
| mechanical service life (switching cycles) typical | 10000 |
| fastening method | 2 OR 3 POINT MOUNTING HOLES |
| number of poles | 3 |
| ampacity | 60 A |
| supply voltage frequency rated value 50/60 Hz | Yes |
| voltage between phase and phase rated value | 600 V |
| switching capacity active power | 3 W |
| ambient temperature during operation maximum | 120 °C |
| ambient temperature during operation minimum | -20 °C |
| product brand name | SIEMENS |
| product type designation | ENCLOSED/SAFETY SWITCH |
| design of the housing | TYPE 1 |
| material | STEEL |
| certificate of suitability | UL |

last modified: 3/23/2020 🖸