

NOTES:

1. MAIN CONDUIT BOX MAY BE ROTATED IN 90~INCREMENTS
2. STANDARD PRODUCT USE BI-DIRECTIONAL FAN. OPPOSITE ROTATION AVAILABLE ONLY BY CONNECTION CHANGE.
3. KEY DIMENSIONS EQUAL 0.75" x 0.75" x 5.709" (MOTOR SUPPLIED WITH KEY)

UNITS: mm [INCHES]

TOSHIBA RESERVES THE RIGHT TO MAKE CHANGES OF TECHNICAL IMPROVEMENT WITHOUT NOTICE. DO NOT USE FOR CONSTRUCTION, INSTALLATION, OR APPLICATION PURPOSES UNLESS THE DRAWING IS CERTIFIED.

404T TEFC FRAME F2 ASSEMBLY		TOLERANCES						Tosh-ECO owp
MDSLE021-12		.X .1						
		.XX .03						
TOSHIBA TOSHIBA INTERNATIONAL CORPORATION		.XXX .005						DRAWN BY: Lin Qingliu CHECK BY: Cai Zhenqiang APPROVED BY: Li Zhuoqing www.toshiba.com/ind
		.XXXX .0005						
		MAXIMUM MOTOR WEIGHT						
		lbs.						
		kgs.		0	FIRST ISSUE	Lin Qingliu	03/14/17	
				NO	REVISION	DRAWN BY	DATE	CHECK



Issued Date	3/14/2017	Transmit #	
Issued By	Lin Qingliu	Issued Rev	0

TYPICAL MOTOR PERFORMANCE DATA

Model: OW22

HP	kW	Pole	FL RPM	Frame	Voltage	Hz	Phase	FL Amps
60	45	6	1105	404T	230/460	60	3	152/76
Enclosure	IP	Ins. Class	S.F.	Duty	NEMA Nom. Eff.	NEMA Design	kVA Code	Ambient (°C)
TEFC	55	F	1.15	CONT	-	D	G	40

Load	HP	kW	Amperes(460)	Efficiency (%)	Power Factor (%)
Full Load	60	44.74	76.4	87.5	84.0
¾ Load	45.00	33.56	59.2	89.0	80.0
½ Load	30.00	22.37	44.6	90.0	70.0
¼ Load	15.00	11.19	34.3	87.0	47.0
No Load			28.0		4.8
Locked Rotor			435		42.3

Torque				Rotor wk² Inertia (lb-ft²)
Full Load (lb-ft)	Locked Rotor (% FLT)	Pull Up (% FLT)	Break Down (% FLT)	
285	275	289	294	49.96

Safe Stall Time(s)		Sound Pressure dB(A) @ 1M	Bearings*		Approx. Motor Weight (lbs)
Cold	Hot		DE	NDE	
20	9	73	6316/C3	6316/C3	1137

*Bearings are the only recommended spare part(s).

Motor Options:

Customer	
Customer PO	
Sales Order	
Project #	

Tag:

All characteristics are average expected values. The declared locked rotor current has a tolerance of 20%.

TOSHIBA INTERNATIONAL CORPORATION · HOUSTON, TEXAS U.S.A.

Engineering		Doc. Written By	P. Anderson	Doc.# / Rev	MDSLE021-12 / 0
Engr. Date		Doc. Approved By	PAA	Doc. Issued	3/14/2017



Issued Date	3/14/2017	Transmit #	
Issued By	Lin Qingliu	Issued Rev	0


SPEED TORQUE/CURRENT CURVE

Model: OW22

HP	kW	Pole	FL RPM	Frame	Voltage	Hz	Phase	FL Amps
60	45	6	1105	404T	230/460	60	3	152/76
Enclosure	IP	Ins. Class	S.F.	Duty	NEMA Nom. Eff.	NEMA Design	kVA Code	Ambient (°C)
TEFC	55	F	1.15	CONT	-	D	G	40
Locked Rotor Amps	Rotor wk ² Inertia (lb-ft ²)	Torque						
		Full Load lb-ft (lb-ft)	Locked Rotor (%)	Pull Up (%)	Break Down (%)			
435	49.96	285	275	289	294			

CHARACTERISTIC CURVES RELATED TO SPEED

Three-phase induction motor-Squirrel cage rotor



Customer		wk ² Load Inertia (lb-ft ²)	-
Customer PO		Load Type	-
Sales Order		Voltage(%)	100
Project #		Accel. Time	-

Tag: _____

All characteristics are average expected values.

TOSHIBA INTERNATIONAL CORPORATION · HOUSTON, TEXAS U.S.A.

Engineering		Doc. Written By	P. Anderson	Doc.# / Rev	MDSLE021-12 / 0
Engr. Date		Doc. Approved By	PAA	Doc. Issued	3/14/2017

TOSHIBA

Issued Date 3/14/2017

Transmit #

Issued By Lin Qingliu

Issued Rev 0

NAMEPLATE DATA

Model: OW22

HP	kW	Pole	FL RPM	Frame	Voltage	Hz	Phase	FL Amps
60	45	6	1105	404T	230/460	60	3	152/76
Enclosure	IP	Ins. Class	S.F.	Duty	NEMA Nom. Eff.	NEMA Design	kVA Code	Ambient (°C)
TEFC	55	F	1.15	CONT	-	D	G	40

Type: _____

Form: _____

Drive End Bearing: 6316/C3

Non-Drive End Bearing: 6316/C3

Power Factor: 84.0

Max Safe RPM: 1980

Comments 1: _____

Comments 2: _____

Comments 3: _____

Comments 4: _____

Customer

Customer PO

Sales Order

Project #

Tag:

All characteristics are average expected values.

TOSHIBA INTERNATIONAL CORPORATION · HOUSTON, TEXAS U.S.A.

Engineering		Doc. Written By	P. Anderson	Doc.# / Rev	MDSLE021-12 / 0
Engr. Date		Doc. Approved By	PAA	Doc. Issued	3/14/2017



Issued Date 3/14/2017

Transmit #

Issued By Lin Qingliu

Issued Rev 0

SPARE PARTS LIST*

Model: OW22

HP	kW	Pole	FL RPM	Frame	Voltage	Hz	Phase	FL Amps
60	45	6	1105	404T	230/460	60	3	152/76
Enclosure	IP	Ins. Class	S.F.	Duty	NEMA Nom. Eff.	NEMA Design	kVA Code	Ambient (°C)
TEFC	55	F	1.15	CONT	-	D	G	40

Bearings DE 6316/C3

Bearings NDE 6316/C3

*Bearings are the only recommended spare part(s).

Other than the grease used for regreasable bearings and the oil used for oil-lubricated bearings, Toshiba advises that there are no "use" parts. The only insurance spares that Toshiba suggests for these squirrel-cage induction motors are industry-standard and commercially available off-the-shelf bearings as noted above.

Motor components such as terminal boxes, fan covers and other machined parts are available on special request. In these cases, please advise our order entry department of the model and serial numbers found on the motor nameplate and a description of the needed components. With this information they will be able to furnish the current part number, price and availability.

Note: Our internal part numbers are subject to change without notice and are not published.

Customer	
Customer PO	
Sales Order	
Project #	

Tag:

All characteristics are average expected values.

TOSHIBA INTERNATIONAL CORPORATION · HOUSTON, TEXAS U.S.A.

Engineering		Doc. Written By	P. Anderson	Doc.# / Rev	MDSLE021-12 / 0
Engr. Date		Doc. Approved By	PAA	Doc. Issued	3/14/2017


Motor Connection Diagrams

12 Leads


Dual Voltage

Across-the-Line Starting / Running
Connections

Low Voltage Delta



High Voltage Delta



Switch L1 and L2 to reverse rotation