

DC Surge Protector SPD SXRR Indoor AAR Terminal 14 Vdc, Single-Mode, 20 kA SASD, GDT

1101-1082 SXRR T50



Features

- SASD and SASD/GDT Hybrid Surge Protection Options
- Suppression Status Indicator
- AAR Terminal Mount

Applications

- Industrial Automation
- Controls & Sense Loops
- Telecommunications Base Stations
- IT & Data Centers
- Wastewater Treatment
- Rail
- Oil & Gas
- LED Lighting

Description

DC surge protector (also known as SPD or lightning protector) 1101-1082 from Transtector is an AAR terminal style SPD that utilizes state of the art SASD, GDT technology to protect critical equipment that operates on a 14 Vdc electrical service. This surge protector provides effective protection against electrical transient surges that are generated both by external lightning events and by internal switching events and supports long-term system reliability by safely shunting high amounts of transient energy while maintaining a very low clamping voltage. Transtector DC surge protectors are available in stock with same day shipping.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Service Voltages		14		Vdc
Maximum Continuous Operating Voltage (MCOV)				
MCOV DC			50	Vdc

Surge Protection Specification

Description	Minimum	Typical	Maximum	Units
Surge Protection Technology		SASD, GDT		
Surge Protection Modes		Signal to GND		
Response Time			5	ns
8/20 μ s Surge Current			20	kA
VPL 8/20 μ s L-G			290 @ 20kA	Vpk

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications:
[DC Surge Protector SPD SXRR Indoor AAR Terminal 14 Vdc, Single-Mode, 20 kA SASD, GDT 1101-1082](#)

DC Surge Protector SPD SXRR Indoor AAR Terminal
14 Vdc, Single-Mode, 20 kA SASD, GDT

1101-1082
SXRR T50



Mechanical Specifications

Size

Height	2.68 in	[68.07 mm]
Width	1.53 in	[38.86 mm]
Depth	1.27 in	[32.26 mm]
Weight	1 lbs	[453.59 g]
Housing Material and Plating	Polyolefin	

Environmental Specifications

Temperature

Operating Range	-40 to +85 deg C
Storage Range	-40 to +85 deg C
Humidity	95% non-condensing

Installation

Mount Type	AAR Terminal Block
------------	--------------------

Transtector Systems specializes in protection of highly sensitive, low voltage equipment through its patented, non-degrading silicon diode technology and custom filters. Our power quality expertise translates into a diverse product offering including AC, DC, and signal applications as well as integrated cabinets, power distribution panels and EMP hardened devices.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [DC Surge Protector SPD SXRR Indoor AAR Terminal 14 Vdc, Single-Mode, 20 kA SASD, GDT 1101-1082](https://www.transtector.com/dc-surge-protector-spd-sxrr-indoor-aar-1101-1082-p.aspx)

URL: <https://www.transtector.com/dc-surge-protector-spd-sxrr-indoor-aar-1101-1082-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Transtector reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Transtector does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Transtector does not assume any liability arising out of the use of any part or documentation.

1101-1082 CAD Drawing

