

AC Surge Protector SPD SP PLUS Brick 240 Vac
Single-Phase MOV 100 kA, TAA

B70-00-6001
LEA SP 100 240-1P



Features

- High Capacity MOV Protection
- Suppression Status LEDs
- Dry Contact Remote Annunciation Wire Leads
- Wall Mount
- Audible Alarm Switch

Applications

- Electrical Panelboards
- Industrial Automation
- Communications Base Stations
- IT & Data Centers
- Switchgear
- Motor Control Centers
- Automatic Transfer Switches
- Wastewater Treatment
- Oil & Gas
- LED Lighting
- Schools
- Hospitals

Description

AC surge protector (also known as SPD or lightning protector) B70-00-6001 from Transtector is a brick style SPD that utilizes state of the art MOV technology to protect critical equipment that operates on a 240 Vac Single-Phase electrical service. This surge protector provides effective protection against electrical transient surges that are generated both by external lightning events and by internal switching events and supports long-term system reliability by safely shunting high amounts of transient energy while maintaining a very low clamping voltage. Transtector AC surge protectors are available in stock with same day shipping.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Service Voltages		240		Vac
Service Type		Single-Phase		
Frequency	50		60	Hz
Maximum Continuous Operating Voltage (MCOV)				
L - N			276	Vac
L - G			276	Vac

Surge Protection Specification

Description	Minimum	Typical	Maximum	Units
Surge Protection Technology		MOV		
Protection Modes		L-N, L-G		

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications:
[AC Surge Protector SPD SP PLUS Brick 240 Vac Single-Phase MOV 100 kA, TAA B70-00-6001](#)

AC Surge Protector SPD SP PLUS Brick 240 Vac
 Single-Phase MOV 100 kA, TAA



B70-00-6001
LEA SP 100 240-1P

8/20 μ s Surge Current		100	kA
Nominal Discharge Current Rating (In)	20		kA
VPR 8/20 μ s			
L - N		1,000	Vpk
L - G		900	Vpk
N - G		1,000	Vpk
Response Time		25	ns
SCCR (Short Circuit Current Rating)	100		kAIC

Mechanical Specifications

Size

Height	6.3 in	[160.02 mm]
Width	6.3 in	[160.02 mm]
Depth	3.5 in	[88.9 mm]
Weight	3 lbs	[1.36 kg]

Environmental Specifications

Temperature Range (Operational)	-40 to +85 deg C
Environmental Protection Rating	NEMA 1
Humidity	95% non-condensing

Installation

Mount Type	Panel
------------	-------

Compliance Certifications

TAA Compliant	Yes
Certifications	IEEE Category C High and B Medium

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications:
[AC Surge Protector SPD SP PLUS Brick 240 Vac Single-Phase MOV 100 kA, TAA B70-00-6001](#)

AC Surge Protector SPD SP PLUS Brick 240 Vac
Single-Phase MOV 100 kA, TAA

B70-00-6001
LEA SP 100 240-1P



Transtector Systems specializes in protection of highly sensitive, low voltage equipment through its patented, non-degrading silicon diode technology and custom filters. Our power quality expertise translates into a diverse product offering including AC, DC, and signal applications as well as integrated cabinets, power distribution panels and EMP hardened devices.

Click the following link (or enter part number in “SEARCH” on website) to obtain additional part information including price, inventory and certifications: [AC Surge Protector SPD SP PLUS Brick 240 Vac Single-Phase MOV 100 kA, TAA B70-00-6001](#)

URL: <https://www.transtector.com/ac-surge-protector-spd-sp-plus-brick-b70-00-6001-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Transtector reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Transtector does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Transtector does not assume any liability arising out of the use of any part or documentation.

B70-00-6001 CAD Drawing

REVISIONS		
REV.	DESCRIPTION	DATE
A	INITIAL RELEASE	1/22/19
		APPROVED DWR

Isometric View: Shows the device with "COLOR CODED SERVICE WIRE LEADS" on top. Dimensions: 3.50 [88.9] (width), 6.30 [160] (height).

Side View: Shows the "CONDUIT HUB" on the left and "AUDIBLE ALARM SWITCH" on the right. Dimension: 6.30 [160] (height).

Front View: Shows "REMOTE SUPPRESSION STATUS WIRE LEADS" on the left, "4X WALL MOUNTING HOLES" at the corners, and "SUPPRESSION STATUS LED" on the right. Dimension: 6.30 [160] (height).

		THE INFORMATION AND DESIGN IN THIS DOCUMENT IS THE PROPERTY OF TRANSTECTOR CORPORATION. ALL RIGHTS RESERVED.	
10701 AIRPORT ROAD, HAYDEN, ID, 83835 PHONE: 1.208.635.6400 1.800.882.9110 FAX: 1.208.955.2041 www.transector.com e-mail: sales@transector.com		SHEET 1 OF 1 SCALE 1:3	REV A
UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES DIMENSIONS IN [] ARE MILLIMETERS	TOLERANCES: .X±.2 [5.08] XX±.01 [.25] XXX±.005 [.13]	FRACTIONS ±.1/32 ANGLES ±1°	ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY. THIRD-ANGLE PROJECTION
	SIZE CAGE A 30992	DRAWN BY HMB	PART NUMBER B70-00-6001

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.

T-Rev A