


Namenschlüssel / naming
SHL-SMT 5.00/0X GX X.XXX



- ① Stifleiste / pin header surface mounting technology
- ② Raster / pitch 5.00mm
- ③ Polzahl / no. of poles 02 / 03 / 04
- ④ Bestueckungsseite / assembly side GL=left side / GR=right side
- ⑤ Pinlaenge / pin length 1.5mm / 3.2mm / 4.2mm / 5.9mm
- ⑥ Verpackung / packaging RL=reel / BX=box

General Tolerances: <input type="checkbox"/> WN700144-W.. <input type="checkbox"/> WN 212010 <input type="checkbox"/> ISO 2768-mK		Tolerances ISO 8015	
Changes: EC00005543			
Part No. 1163943			
Drawings Customer		70315 ② <small>Drawing no. Index</small>	
Drawn	Miske, Anna	Scale: 1/1 Sheet 1 / 1	
Responsible	Niggemann, Matthias	CH20M A 0V PCB-SHL POSITION PIN HEADER POSITION STIFTLLEISTE	
Approved	Püschner, Klaus		
		16.09.2021	

The reproduction, distribution and utilization of this document as well as the communication of its contents to others without explicit authorization is prohibited. Offenders will be held liable for the payment of damages. Weidmüller exclusively reserves the right to file for patents, utility models or designs.

© Weidmüller Interface GmbH & Co. KG